

MODEL # SCAS-II-TC-SMART-MM

SPECIFICATIONS


THE OLYMPUS II TURBO CHILL AIR SCREEN MICRO MARKET IS A UNIQUE PATENTED DESIGN THAT GIVES OPERATORS THE FLEXIBILITY TO PROGRAM THEIR PARAMETERS INTO THE UNIT FOR MONITORING FOOD TEMPERATURES AT SPECIFIC LEVELS. UNIT IS PRESET WITH PROBE BUILT INTO A SMART CONTROLLER, THAT IF PRODUCT REACHES 39.5 F, THE MOTORIZED DOOR WILL CLOSE AND ACTIVATE TURBO CHILL UNTIL THE PRODUCT REACHES 37.5 F. THE DOOR WILL THEN AUTOMATICALLY RE-OPEN WHEN FINISHED. THERE IS ALSO AN ADDED STANDARD FEATURE OF MANUAL-OVERRIDE TO BYPASS THE CONTROLLER (IF NEEDED).

NOTE: If unit is lined-up with Flexeserve Heated, overall depth will increase to 34"

Available lengths: 60"

Available depths: 32"

Available heights: 78"



STANDARD FEATURES

- DOE 2017 Compliant
- Motorized Roll Down Locking Security Cover
- (NEW) Smart Controller Food Product Simulator Probe and Safety Sensor
- Unique Internal Baffle Design for Compressor Noise Reduction
- Front Air Intake with Top Rear Air Discharge for Zero Clearance
- Red Indicator Light Alerts Operator if Condenser Requires Cleaning
- Removable Stainless Steel Deck Pan with Hemmed Edge to Contain Spills
- Standard Grade Laminate Exterior
- Top bracket designed to accommodate header panel
- Self-Contained Refrigeration
- Standard Air Screen Storage Unit
- Easy Slide-Out Condensing Unit
- Squared Top Canopy
- Metal Frame Base Construction with Lift-Out Louvered Air Grill for Easy Access to Compressor
- Brushed Stainless Steel Interior Ends
- Stainless Steel Perforated Interior Back Panel
- LED Top Canopy Light
- (3) Adjustable Stainless Steel Extra Deep Shelves
- Energy Efficient LED Lighting
- Electronic Digital Control and Defrost Termination
- 8' Cord and Plug
- ETL Listed in Accordance with UL 471 and NSF 7 Standards
- Conforms to NSF STD 7 Type II Refrigeration
- Environmentally Safe Refrigerant
- 1 Year Parts and Labor Warranty
- Floor Drain Required
- 5 Year Compressor Warranty

OPTIONAL FEATURES

- Condensate Evaporator Pan
- 24" High Header Panel (Graphics by others)
 - 16" High Lightbox Insert Header
 - Backlit top header
- Stainless Steel Exterior Finish
 - #4
 - #6
 - #8
- Remote Refrigeration (Consult Factory)
- Mirrored Polished Stainless Steel Interior Ends (#8 Finish)
- Mirrored Polished Stainless Steel Perforated Interior Back Panel (#8 Finish)
- Mirrored Polished Stainless Steel Shelves (#8 Finish)

ADDITIONAL OPTIONAL FEATURES

- Front Decorative Panels (Remote Refrigerated Units Only, Consult Factory)
- Special Laminates
- Wood Veneers (Stained & Sealed)
- Wire Shelves:
 - White
 - Black
 - Chrome
- Casters (Increases Height by 6")
- Adjustable Legs (Consult Factory for Sizes)
- Powder Coated Interior Back Panel and Hardware:
 - Black
 - White
 - Custom Color
- Finished Back with Black Air Grill
- Stainless Steel Louvered Air Grill
- Front Merchandising Wire Baskets (Slat Wall Exterior Required, Consult Factory)
 - Style A
 - Style B
 - Style C
- Front Merchandising Tables & Ladders (Top Mount or Remote units only)
 - Style A
 - Style B
 - Style C
 - Style D
 - Style E
 - Style F
 - Style G
 - Style H
 - Style I
 - Style J



Conforms to UL Standard 471, and NSF Standard 7; Certified To CSA Standard C22.2 No. 120




CALL TOLL FREE: 800-525-3692 (609-714-2330)

FAX: 609-714-2331 www.rpiindustries.com

220 ROUTE 70, MEDFORD, NJ 08055

MODEL # SCAS-II-TC-SMART-MM



SELF - CONTAINED - Floor Drain

MODEL	L	D	H	HP	VOLT	AMP	PLUG	WT	REFRIG.
SCAS60R-II TC SMART-MM	60	32	78	1 1/4	115/208-230 4 wire	12.1	L14-20P	1178	404A

SELF - CONTAINED - With Evaporator Pan


MODEL	L	D	H	HP	VOLT	AMP	PLUG	WT	REFRIG.
SCAS60R-II TC SMART-MM	60	32	78	1 1/4	115/208-230 4 wire	16.9	L14-30P	1178	404A

NOTE: A minimum of 18" clearance needed above unit for air discharge for self contained units.

* (If graphic top header is included, minimum of 18" clearance required above top header.

* 448a refrigeration available at no additional cost - please specify

8' Cord and Plug



Electrical & Plumbing locations



Conforms to UL Standard 471, and NSF Standard 7; Certified To CSA Standard C22.2 No.120



RPI refrigerated merchandisers configured for sale in the United States meet or surpass the requirements of the DOE 2017 energy efficiency standards

1. Refrigeration System is designed so air will flow front to rear. Unobstructed air flow must be maintained to ensure unit performance and maintain warranty.

2. The SCAS-II TC SMART merchandiser is designed for use in locations where temperature and humidity do not exceed 80 Degrees Fahrenheit and 60% R.H. Locate away from direct sunlight, rapid air currents and extreme temperature changes. Exposure to air currents from ceiling fans, air conditioners, ovens, etc. will disrupt the case's air curtain and refrigerated zone within.

Any adverse field conditions stated above will void warranty.

RPI in line with it's current policy to continually improve it's product reserves the right to change materials and specifications without notice.

CALL TOLL FREE: 800-525-3692 (609-714-2330)

FAX: 609-714-2331 www.rpiindustries.com

220 ROUTE 70, MEDFORD, NJ 08055

