

## MODEL # VIAS-SL INS SLANTED GLASS

### SPECIFICATIONS

The Vienna Series VIAS-SL INS Slide-in with rear air ventilation kit is a self-service "Grab and Go" style refrigeration merchandiser, featuring a slanted glass profile, with insulated glass side panels. Unit is available in choice of three heights with hinged see-through access doors. When being used as a "slide-in" please advise if counter height is 34" or 36". Optional 6" or 8" stainless steel adjustable legs or 6" casters are available for all slide-in style models.



- Available lengths:  31 1/2"  44 1/4"  57 1/8"  69 7/8"  
 Available depths:  27 3/8"  
 Available heights:  21 5/8"  28 3/8"  35"

### STANDARD FEATURES

- Slanted Glass Profile
- 304 Stainless Steel Exterior
- Tempered Glass Top Panel, Insulated Glass Side Panels,
- Hinged Rear See-Through Access Doors
- Fully adjustable Tempered Glass Shelves (tiltable to 7 degrees)
- Easy Removable Deck Pans for Cleaning
- Programmable Digital Refrigeration Controller
- Self-Contained Refrigeration with Integrated Slide-In Base
- Rear Air Ventilation Kit
- Energy Efficient LED Lighting (Plug-In)
- Fan Assisted Cooling System
- Lift-Up Evaporator
- 5 Year Compressor Warranty
- ETL Listed in Accordance with UL 471 and NSF 7 Standards
- Environmentally Safe Refrigerant
- Designed for Floor Drain

### OPTIONAL FEATURES

- Drop-In Style (Consult Factory for Additional Information)
- Remote Refrigeration
- Powder Coat Finish
- Front Air Vent with Solid Rear (for against the wall installation)
- Rear Cutting Board
- Mirrored Hinged Rear Access Doors
- Pull down night curtain
- Removable Acrylic Locking Night Cover
- Rear-Mounted Door Locks
- Integrations Modular Counter (Consult Factory)
- Adjustable Legs & Casters (Slide-In Units)
  - 6" Legs  8" Legs
  - 6" Casters
- Hot Gas Evaporation (self-contained only)
- Condensate Evaporator Pan (Consult Factory)



Conforms to UL Standard 471, and NSF Standard 7; Certified To CSA Standard C22.2 No.120

MODEL	L	D	H	HP	VOLT	AMPS	PLUG	WT	REFRIG.	DROP IN C/O SIZE	SLIDE IN C/O SIZE
VIAS2-20-R-SL-SC INS	31 1/2	27 3/8	21 5/8	1/2	115	8.8	5-15P	462	R448A	29 1/4 x 26 3/8	29 1/4 x VARIES
VIAS3-20-R-SL-SC INS	44 1/4	27 3/8	21 5/8	1/2	115	9.1	5-15P	506	R448A	42 1/8 x 26 3/8	42 1/8 x VARIES
VIAS4-20-R-SL-SC INS	57 1/8	27 3/8	21 5/8	3/4	115/230	4.9	L14-20P	572	R448A	54 7/8 x 26 3/8	54 7/8 x VARIES
VIAS5-20-R-SL-SC INS	69 7/8	27 3/8	21 5/8	7/8	115/230	6.6	L14-20P	638	R448A	67 5/8 x 26 3/8	67 5/8 x VARIES
VIAS2-27-R-SL-SC INS	31 1/2	27 3/8	28 3/8	1/2	115	9.7	5-15P	484	R448A	29 1/4 x 26 3/8	29 1/4 x VARIES
VIAS3-27-R-SL-SC INS	44 1/4	27 3/8	28 3/8	3/4	115/230	5.6	L14-20P	528	R448A	42 1/8 x 26 3/8	42 1/8 x VARIES
VIAS4-27-R-SL-SC INS	57 1/8	27 3/8	28 3/8	7/8	115/230	7.7	L14-20P	594	R448A	54 7/8 x 26 3/8	54 7/8 x VARIES
VIAS5-27-R-SL-SC INS	69 7/8	27 3/8	28 3/8	1 1/4	115/230	9.1	L14-20P	660	R448A	67 5/8 x 26 3/8	67 5/8 x VARIES
VIAS2-34-R-SL-SC INS	31 1/2	27 3/8	35	3/4	115/230	5.4	L14-20P	528	R448A	29 1/4 x 26 3/8	29 1/4 x VARIES
VIAS3-34-R-SL-SC INS	44 1/4	27 3/8	35	7/8	115/230	7.3	L14-20P	572	R448A	42 1/8 x 26 3/8	42 1/8 x VARIES
VIAS4-34-R-SL-SC INS	57 1/8	27 3/8	35	1 1/4	115/230	9.0	L14-20P	638	R448A	54 7/8 x 26 3/8	54 7/8 x VARIES
VIAS5-34-R-SL-SC INS	69 7/8	27 3/8	35	1 1/4	115/230	9.6	L14-20P	704	R448A	67 5/8 x 26 3/8	67 5/8 x VARIES

CALL TOLL FREE: 800-525-3692 (609-714-2330)



FAX: 609-714-2331 [www.rpiindustries.com](http://www.rpiindustries.com)

220 ROUTE 70, MEDFORD, NJ 08055



INDUSTRIES, INC. v10\_19\_23


## MODEL # VIAS-SL INS SLANTED GLASS



LARGEST DIMENSION REPRESENTS OUTSIDE FLANGE

1. A 1 1/8" diameter drain is provided. The drain **MUST** be connected to a floor drain or storage container **AT TIME OF INSTALLATION**.
2. Ventilation louvers **MUST** be provided in the cabinet or counter and located so to provide full ventilation for the condensing unit.
3. The VIAS-SL INS merchandiser is designed for use in locations where temperatures and humidity do not exceed 75 degrees and 55% R.H. Locate away from direct sunlight, rapid air currents and extreme temperature changes. Exposure to air currents from ceiling fans, air conditioners, ovens, etc. will disrupt the cases air current and refrigeration zone within. Any adverse field conditions stated above will void warranty.

RPI in line with it's policy to continually improve it's product reserves the right to change materials and specifications without notice.



**Electrical & Plumbing locations**